MOTION CONTROL APPARATUS AND METHOD FOR AUTOMOTIVE VEHICLE

BACKGROUND OF THE INVENTION:

5 ### Field of the invention

[0001]   The present invention relates to motion control apparatus and method for an automotive vehicle which are capable of controlling a vehicular motion during a steering maneuver input on front road

10 wheels.

Description of the related art

[0002]   A Japanese Patent Application First Publication No. Heisei 10-007010 published on January 13, 1998 (which corresponds to a United States Patent

15 No. 5,957,987 issued on September 28, 1999) exemplifies a previously proposed vehicular motion control apparatus. In the above-identified Japanese Patent Application First Publication, a vehicular yaw rate and so on are controlled during a steering

20 operation (maneuver) so that a vehicular stability during a steering wheel operation is maintained. Specifically, a target yaw rate for a response characteristic related to a plane motion of the vehicle on the basis of the steering angle and the

25 vehicular velocity to coincide with a predetermined response characteristic is calculated, a rear road wheel steering angular command value required to make the yaw rate developed on the vehicle coincident with its target value is calculated in accordance with a

30 motion equation based on a vehicular specification value. Rear road wheel actual steering angles are controlled to follow a rear road wheel steering angle

command value. Thus, this control results in a yaw motion in accordance with a target yaw rate.

[0003]   The target yaw rate is calculated by setting a response characteristic of the target yaw
5   rate with respect to a change in the steering angle as a first order or second order transfer function and presetting a vehicle speed dependent constant in accordance with a vehicle speed. Thus, a steering response characteristic of the yaw rate during a low
10 speed run is maintained and a vehicular motion which is superior in a steering response characteristic and stability without giving a sense of incompatibility to a vehicle driver during a high speed run can be achieved.

15 **SUMMARY OF THE INVENTION:**
[0004]   However, in the above-described vehicular motion control apparatus, the vehicular speed dependent constants are stored as skip values (discrete values and not continuous values) as a map
20 stored previously for each vehicle speed. In a case where the vehicle speed during the calculation of the target yaw rate is not coincident with a point on a map axle, a straight line (linear) interpolation is carried out on the basis of points mutually adjacent
25 points on the map to calculate the corresponding vehicle speed dependent constant. Hence, an error due to the execution of the straight line (linear) interpolation gives an ill influence on the target yaw rate. Consequently, there is a high possibility
30 of giving an ill influence on the rear road wheel steering angle. Hence, in a case where the vehicular velocity is varied during the steering operation such as a turning braking, the rear road wheel steering

angles provide motions other than a desired motion so
that there is a possibility that the driver gives an
unpleasant feeling (the sense of incompatibility).

[0005]   It is, therefore, an object of the present
invention to provide vehicular motion control
apparatus and method which are capable of controlling
stably a motion of the vehicle without giving the
sense of incompatibility to the driver, even if the
vehicle velocity (vehicle speed) is varied during the
vehicular motion control in the vehicular motion
control apparatus.

[0006]   The above-described object can be achieved
by providing a vehicular motion control apparatus,
comprising: a steering angle detecting section that
detects a vehicular steering angle; a vehicle speed
detecting section that detects a vehicle speed; a
vehicular motion control mechanism that is capable of
controlling a vehicular motion; a state detecting
section that detects a state of the vehicular motion
control mechanism; a vehicular motion target value
calculating section that calculates a target value of
the vehicular motion for a response characteristic on
a vehicular plane motion to be enabled to provide a
predetermined response characteristic on the basis of
detection values of the steering angle and the
vehicle speed and vehicle speed dependent constants
preset in a form of a map for each vehicle speed; a
control command value calculating section that
calculates a vehicular motion control mechanism
command value required to achieve the target value of
the vehicular motion; and a servo calculating section
that provides a control signal for a rear road wheel
steering actuator in such a manner that a detection

value of the state of the vehicular motion control
mechanism is made coincident with the motion control
mechanism command value; and a vehicular velocity
variation rate limiter that places a limitation on a
5   vehicle speed variation rate and varies in accordance
with the detection value of the vehicular steering
angle, the vehicular motion target value calculating
section using an output of the vehicular speed
variation rate limiter for a map reference vehicle
10   speed and the control command value calculating
section using the output of the vehicular speed
variation rate limiter to the detection value of the
vehicle speed for a control command value calculation.
[0007]   The above-described object can also be
15   achieved by providing a vehicular motion control
method, comprising: detecting a vehicular steering
angle; detecting a vehicle speed; providing a
vehicular motion control mechanism which is capable
of controlling a vehicular motion; detecting a state
20   of the vehicular motion control mechanism;
calculating a target value of the vehicular motion
for a response characteristic on a vehicular plane
motion to be enabled to provide a predetermined
response characteristic on the basis of detection
25   values of the steering angle and the vehicle speed
and vehicle speed dependent constants preset in a
form of a map for each vehicle speed; calculating a
vehicular motion control mechanism command value
required to achieve the target value of the vehicular
30   motion; and providing a control signal for a rear
road wheel steering actuator in such a manner that a
detection value of the state of the vehicular motion
control mechanism is made coincident with the motion

control mechanism command value; and providing a vehicle speed variation rate limiter to place a vehicle speed variation rate limitation on the detection value of the vehicle speed and varying the vehicle speed variation rate limitation in accordance with the detection value of the vehicular steering angle, at the vehicular motion target value calculation, using an output of the vehicular speed variation rate limiter for a map reference vehicle speed and, at the control command value calculation, using the output of the vehicular speed variation rate limiter to the detection value of the vehicle speed for a control command value calculation.

[0008]   This summary of the invention does not necessarily describe all necessary features so that the invention may also be a sub-combination of these described features.

BRIEF DESCRIPTION OF THE DRAWINGS:

[0009]   Fig. 1 is a rough configuration view of an automotive vehicle to which a first preferred embodiment of a vehicular motion control apparatus is applicable.

[0010]   Fig. 2 is a schematic view of a steering angle controller (controller) of the vehicular motion control apparatus in the first embodiment shown in Fig. 1.

[0011]   Fig. 3 is a circuit block diagram representing a structure of a target value generating section in the vehicular motion control apparatus in the first embodiment shown in Fig.

[0012]   Fig. 4 is an operational flowchart representing a steering control procedure executed by the controller shown in Fig. 2.

[0013]   Fig. 5 is a vehicle speed-yaw rate gain map used in a steering control of the vehicular motion control apparatus in the first embodiment shown in Fig. 2.

5   [0015]   Fig. 6 is a partially expanded view of the vehicle speed-yaw rate gain map shown in Fig. 5.

[0016]   Fig. 7 is an operational flowchart representing a vehicle speed variation rate limit processing.

10   [0017]   Fig. 8 is a map on the absolute value of a steering angle absolute value-vehicle speed variation limit value used in the motion control apparatus in the first embodiment.

[0018]   Fig. 9 is an operational flowchart

15   representing a rear road wheel steering angle calculation processing and correction processing in the first embodiment.

[0019]   Figs. 10A, 10B, 10C, 10D, 10E, and 10F are integrally a timing chart of each control signal in a

20   case where no vehicle speed limitation is placed.

[0020]   Figs. 11A, 11B, 11C, 11D, 11E, and 11F are integrally a timing chart of each control signal in a case where the vehicle speed limitation is placed.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS:

25   [0021]   Reference will hereinafter be made to the drawings in order to facilitate a better understanding of the present invention. Hereinafter, preferred embodiments of a vehicular motion control apparatus according to the present invention will be

30   described. However, the present invention is not limited to these embodiments.

[0022]   (First Embodiment)

Fig. 1 is a whole system configuration view representing a basic structure of a vehicular motion control apparatus in a first preferred embodiment according to the present invention.

[0023]   A steering angle variable mechanism 3 includes: knuckle arms 5L and 5R attached onto left and right rear road wheels 2L and 2R; king pin axles 6L and 6R; ball joints 7L and 7R; a tie rod 8 connected to knuckle arms 5L and 5R and formed about ball joints 7L and 7R; a slip screw 9 formed on tie rod 8; and a nut 10 having outer teeth on an outer peripheral surface thereof, the slip screw 9 being formed on tie rod via king pin axles 6L, 6R and ball joints 7L and 7R between knuckle arms 5L and 5R; and outer teeth 12 attached on a revolving axle of a driving motor 11 constituted by a stepping motor and which is meshed with the outer teeth of nut 10. A revolution drive of driving motor 11 moves tie rod 8 in the leftward-and-rearward direction to steer rear left-and-right wheels 2L and 2R. It is noted that a reference numeral 13 denotes a return spring for tie rod 8 to be returned to a neutral position. It is also noted that, in Fig. 1, a reference symbol S denotes a steering wheel of a vehicular steering system, 1L and 1R denotes front left and right road wheels, and 2L and 2R denote rear left and right road wheels.

[0024]   Fig. 2 shows a functional block diagram of controller 4 shown in Fig. 1. As shown in Fig. 2, a controller 4 includes a vehicular motion target value setting section (vehicular target value calculating section) 41 which receives a front road wheel steering angle detection value θ from a front road

wheel steering angle sensor 14 and a vehicle speed
detection value V from vehicle speed sensor 16 and
calculates a target yaw rate $\Psi'*$ as a vehicular
motion target value and a target yaw angular

5   acceleration $\Psi''*$. In addition, a target rear road
wheel steering angle calculating section 42 which
calculates a target rear road wheel steering angle
$\delta*$ on the basis of target yaw rate $\Psi'*$ and target yaw
angular acceleration $\Psi''*$ derived from vehicular

10   motion target value setting section 41, detection
value of the front steering angle θ and vehicular
velocity detection value V is functionally provided
in controller 4. Controller 4 includes a
microcomputer having a CPU (Central Processing Unit),

15   a ROM (Read Only Memory), a RAM (Random Access
Memory), an Input Port, an Output Port, a common bus,
and so forth. Furthermore, controller 4 includes a
rear road wheel steering angle servo amplifier
(amplifying or calculating) section 43 which supplies

20   a control signal to a rear road wheel steering angle
steering actuator 11 (namely, drive motor shown in
Fig. 1), the control signal being such that rear road
wheel steering angle detection signal δ is made
coincident with target rear road wheel steering angle

25   $\delta*$.
[0025]   Vehicular velocity motion target value
setting section 41 calculates a target yaw rate (yaw
velocity) $\Psi'*$ as a vehicular motion target value with
respect to a front road wheel angle detection value

30   on the basis of a transfer function between front
road wheel steering angle detection value θ and

target yaw rate $\Psi'*$ shown in the following equation
(1).

$$\varphi'*/\theta = G\Psi' \cdot \left\{ \omega_n^2(n_1 S + 1) \right\}/(S^2 + 2\zeta\omega_n S + \omega_n^2) \quad \cdots\cdots \quad (1),$$

wherein S denotes s Laplace transform operator, $G\Psi'$,

5 ωn, n_1, and ζ denote vehicle speed dependent
constants, namely, $G\Psi'$ denotes a yaw rate gain, ω_n
denotes a natural (or specific) angular frequency, n_1
denotes a zero point corresponding (equivalent) value,
and ζ denotes a damping coefficient. These vehicle

10 speed dependent constants are set on the basis of a
control map representing a correspondent relationship
between a preset vehicle speed and each of the
vehicle speed dependent constants.

[0026]   Fig. 5 typically shows a map representing

15 the relationship between vehicle speed V and yaw rate
gain $G\Psi'$. These vehicle speed dependent constants
are such that yaw rate gain $G\Psi'$ identifies a steady
state gain, namely, a steady state yaw rate with
respect to the steering angle θ, specifies a steady

20 state yaw rate with respect to a steering angle,
specific angular frequency ωn specifies its vibration
frequency, a zero-point equivalent value n_1 denotes a
speed of a rise in a yaw rate with respect to a
change in the steering angle, namely, specifies a

25 rise characteristic of yaw rate, and damping
coefficient ζ specifies a speed of a convergence,
namely, specifies a convergence characteristic of the
yaw rate. Hence, the whole speed dependent constants
are set to be enabled to provide desired response

30 characteristics and the response characteristic of
target yaw rate $\Psi'*$ calculated on the basis of the
preset vehicle speed dependent constants using

equation (1) provide a desired response characteristic.

[0027]   Hence, by setting vehicle speed dependent constants in accordance with the vehicle speed, the response characteristic on target yaw rate $\Psi'*'$ provides response characteristic different in dependence on the vehicle speed. In addition, by individually and independently modifying yaw rate gain $G\Psi'$, specific angular frequency ωn, zero-point equivalent value n_1, and damping coefficient ζ, the response characteristic which is different only in steady state gain or vibration frequency only can be obtained.

[0028]   Fig. 3 shows a block diagram representing a structure of vehicular motion target value setting section 41. In rear road wheel steering angle command value setting (calculating) section 42, target yaw angular acceleration $\Psi''*$ is needed. Hence, after target yaw angular acceleration $\Psi''*$ is calculated, this is integrated to calculate a target yaw rate $\Psi'*$. It is noted that B_0, B_1, F_0, and F_1 in Fig. 3 are values calculated on the basis of the following equations:

$B_0 = \omega_n^2$, $B_1 = 2\zeta\omega_n$, $F_0 = n_1\omega_n^2$, and $F_1 = \omega_n^2 - B_1 \cdot F_1$. In rear road wheel steering command value calculating section 42, a reverse calculation of two degrees of freedom vehicular motion equations causes the rear road wheel steering angle δ which can make target yaw rate $\Psi'*$ coincident with actual yaw rate Ψ' to be calculated so that this provides target rear road wheel steering angle $\delta*$.

$$\delta* = \beta_R + (V_y - L_R \cdot \Psi'*)/V \qquad \ldots (2).$$

$$\beta_R = C_R/K_R$$

$$C_R = (2L_F \cdot C_F - Iz \cdot \Psi'' */2)/L_R$$

$$C_F = eK_F \cdot \beta_F$$

$$\beta_F = \theta/N - (V_y + L_F \cdot \Psi' *)/V$$

5 $$V_y = \int V_y' dt$$

$$V'_y = (2C_F + 2C_R)/M - V \cdot \Psi' *,$$ wherein V_y
denotes a vehicular lateral velocity, $V'_y = dV_y$
(described later), β_F denotes a front road wheel side
slip angle, β_R denotes a rear road wheel side slip
10 angle, C_F denotes a cornering force of front road
wheels, C_R denotes a cornering force of rear road
wheels, K_R denotes a cornering power of a vehicular
rear road wheel, eK_F denotes an equivalent cornering
power of a vehicular front road wheel (although the
15 front road wheel cornering power, a value with a
reduction of the cornering power with respect to the
steering angle due to an influence of steering
rigidity), I_z denotes a yaw inertia moment of the
vehicle, M denotes a vehicular weight, and N denotes
20 a steering gear ratio.

[0029]   Rear road wheel steering angle servo
amplifying section 43 carries out a servo calculation
using a Robust Model Matching Control on the basis of
a deviation between a rear road wheel steering angle
25 command value δ* and a rear road wheel steering angle
detection signal δ of rear road wheel steering angle
sensor (rear road wheel steering angle detecting
section) 17 and the control signal is outputted to
rear road wheel steering actuator 11 constituted by
30 the drive motor. The robust model matching technique
is exemplified by a United States Patent No.
6,175,799 issued on January 16, 2001. Rear road wheel

steering angle servo amplifying section 43, for
example, includes a robust compensator which serves
as an external disturbance estimator and a model
matching compensator which makes whole response

5   characteristic of the rear road wheel steering angle
servo calculating section 43 equal to a response
characteristic of a normal (standard) model, in
order for rear road wheel steering angle servo
calculating section 43 to provide a robust control

10   system to such a variation in the rear road wheel
steering angle value (δ), (the disclosure of the
United States Patent described above is herein
incorporated by reference).

[0030]   Next, an operation of the vehicular motion

15   control apparatus in the first embodiment according
to the present invention will be described below.
Fig. 4 shows an operational flowchart representing a
procedure in accordance with which (vehicular motion)
controller 4 is executed. It is noted that this

20   procedure shown in Fig. 4 is executed for each
predetermined control period (for example, 10
milliseconds).

[0031]   At a step 101, controller 4 reads steering
angle detection value θ from front road wheel

25   steering angle sensor (a vehicular steering angle
detecting section) 14, vehicle speed detection value
V from vehicle speed sensor (vehicle speed detecting
section) 16, and a rear road wheel steering angle
detection signal δ from rear road wheel steering

30   angle sensor 17.

[0032]   At a step 102, controller 4 refers to
control maps each representing a correspondent
relationship between a preset vehicle speed and

corresponding one of the vehicle speed dependent
constants and sets yaw rate gain $G\Psi'$, damping
coefficient ζ, specific angular frequency ω_n, and a
zero-point equivalent (corresponding) value n_1. As
appreciated from Fig. 5, since the values set for
each predetermined value is provided, when the
detected vehicular velocity is rested on a point
except a predetermined vehicular velocity on a map, a
straight line (linear) interpolation derives a value
between the maps so that each vehicle speed dependent
constant is set.

[0033]   A map reference vehicle speed Vmap in which
a limitation is placed on a variation rate of vehicle
speed V without use of the detection value directly
from vehicle speed sensor 2 to refer to each of the
control maps. The detailed description thereof will
be described later.

[0034]   Then, at a step 103, controller 4
calculates target yaw rate $\Psi'*$ on the basis of set
vehicle speed dependent constants, equation (1), and
steering angle detection value θ from the front road
wheel steering angle sensor 14.

[0035]   At a step 104, controller 4 calculates rear
road wheel steering angle command value $\delta*$ which
enables the coincidence of calculated target yaw rate
$\varphi'*$ with actual yaw rate φ'. However, map reference
vehicle speed Vmap is also used for the calculation
of equation (2) described above. The details of map
reference vehicle speed Vmap will be described later.
In addition, if the vehicle speed is lower than a
predetermined vehicle speed B whish represents a low
vehicle speed, the rear road wheel steering angle
command value correction processing to correct rear

road wheel steering angle command value δ* calculated
at a previous control period is executed. The
details of the processing will be described later.

[0036]   At a step 105, controller 4 carries out a

5   servo calculation using, for example, the robust
model matching control on the basis of the deviation
between rear road wheel steering angle command value
δ* and rear road wheel steering angle detection value
δ and calculates the control signal to be outputted

10   to rear road wheel steering actuator 3.

[0037]   (Vehicle speed limiter processing during
vehicle speed dependent calculation)

     Next, the detailed explanation of step 102
shown in Fig. 4 will herein be made. The linear

15   (straight line) interpolation is used to develop an
error when respective vehicle speed dependent
constants are set. Consequently, there is a
possibility that a sense of incompatibility is given
to the driver. The explanation is made on this

20   phenomenon. To simplify this phenomenon, vehicle
speed dependent constants are supposed to be set to
the same values as the vehicle speed dependent
constants that 2WS (rear left and right rear road
wheels 2L and 2R are not steered) vehicle has. In a

25   region equal to or below vehicle speed A shown in Fig.
5, target yaw rate Ψ'* calculated on the basis of
vehicle speed constants becomes equal to the yaw rate
characteristic developed on 2WS (two wheel steering)
vehicle. This target rear road wheel steering angle

30   δ* calculated on the basis of target yaw rate Ψ'*
should be zeroed at a low speed region denoted by
point A in Fig. 5. However, the control map
representing vehicle speed and one of vehicle speed

dependent constants has a value for each
predetermined vehicle speed. Hence, a value between
each vehicle speed point is derived through the
linear interpolation. As shown by a map expanded
view of Fig. 6, a region in which, strictly, an
actual characteristic is not coincident with 2WS
characteristic is present. For example, a difference
$\Delta G\varphi'$ in characteristic between actual 2WS
characteristic and characteristic line by means of
the linear interpolation indicates p when, for
example, vehicle speed is at a speed of a1.
Difference $\Delta G\varphi'$ at a time of vehicle speed of a2
indicates zero. In addition, difference $\Delta G\varphi'$ when
vehicle speed is at a steed of a3 is q ($>$p).
Therefore, as target yaw rate $\varphi'*$ is different from
the yaw rate characteristic developed on 2WS vehicle,
rear road wheel steering angle command value $\delta*$ is
calculated (except zero) having a certain value. This
phenomenon gives the sense of incompatibility to the
vehicle driver (even if the rear road wheel is
developed, the influence is less since the rear road
wheel steering angle is minute and gives a constant
value). However, in a case where the vehicular speed
is varied, the rear road wheel steering angle is
varied (the error with respect to 2WS characteristics
becomes large and/or small); this is varied due to a
compensation for p $\rightarrow$ 0 $\rightarrow$ q or q $\rightarrow$ 0 $\rightarrow$ p) and,
hence, there is a possibility that the sense of
incompatibility is given to the driver).

[0038]   Then, if the vehicle speed at a time of
referring to each of the control maps, each map
representing the correspondence between the detection
value of the vehicle speed and the corresponding one

of the vehicle speed dependent constants, is
moderately varied, an influence caused by the above-
described interpolation error is suppressed.
Specifically, as shown by a vehicle speed variation

5   rate limit map of a steering angle absolute value-to-
vehicular speed variation rate in Fig. 8, a vehicular
speed variation rate limiter is provided for the map
reference vehicle speed and the control command value
calculation vehicle speed. An output of the vehicle

10 speed variation rate limiter is placed to vehicle
speed detection value V may be vehicle speed
dependent constant map refererence vehicle speed Vmap.
Hereinafter, a vehicular speed limiter process in the
calculation of Vmap will be made on the basis of the

15 flowchart of Fig. 7. That is to say, at a step 201,
controller 4 sets a vehicular speed variation rate
limit value dVlimit from an absolute value of
steering angle |θ| as shown in Fig. 8. Since dVlimit
denotes a value varied in accordance with absolute

20 value |θ| of steering angle detection value, the
value of limit value dVlimit is made smaller as
absolute value of steering angle |θ| becomes larger
and limit value of dVlimit becomes larger as absolute
value of steering angle |θ| becomes smaller.

25 [0039]   At a step 202, controller 4 compares the
present value of vehicle speed V(n) presently
detected and (a previous value of) map reference
vehicle speed Vmap(n -1) previously calculated
(before the control period of 10 milliseconds). If

30 present vehicle speed detection value V(n) is larger
than the previous value of the map reference vehicle
speed (Vmap(n-1)) (namely, V > Vmap) at step 202 ,
the routine goes to a step 203. At step 203,

controller 4 compares a first difference of the present value of vehicle speed detection value V(n) from the previous value of map reference vehicle speed Vmap(n-1) (V(n) - Vmap(n-1), namely, V - Vmap) with vehicle speed variation rate limit value dVlimit. If V(n) - Vmap(n-1) > dVlimit (Yes) at step 203, the routine goes to a step 204. If V < Vmap (namely, V(n)< Vmap(n-1) at step 202, the routine goes to a step 205. If the present detection value of vehicle speed V(n) is made equal to the previous value of map reference vehicle speed Vmap (namely, Vmap(n-1)) at step 202 (V = Vmap), the routine goes to a step 207.

[0040]   In details, after, at step 203, controller 4 compares the first difference of the present value of vehicle speed (n) from map reference vehicle speed Vmap(n-1) with vehicular speed variation rate limit value dVlimit and, if V(n) - Vmap(n-1) > dVlimit (Yes) at step 203, the routine goes to a step 204.

[0041]   At step 204, controller 4 sets an addition value of Vmap(n-1) to vehicle speed variation rate limit value of dvlimit as the present value of Vmap(n). On the other hand, If V(n) < Vmap(n-1) at step 202 (namely, V < Vmap) at step 202, the routine goes to a step 205.

[0042]   If a second difference of the present value of vehicle speed V(n) from the previous value of the map reference vehicle speed Vmap(n-1) is larger than limit value dVlimit, namely, if V(n) - Vmap(n-1) > dVlimit (V - Vmap > dVlimit) at step 205 (Yes), the routine goes to a step 206. If V(n) - Vmap(n-1) ≤ dvlimit (No at step 205), the routine goes to step 207. At step 206, controller 4 sets a value of

subtraction of dVlimit from Vmap(n-1) as the present
Vmap(n) (Vmap(n) = Vmap(n-1) -dVlimit). That is to
say, if the variation in vehicle speed V becomes
larger in a decrease direction, variation rate of map

5   reference vehicle speed Vmap is limited by dVlimit.
At step 207, the present detection value of the
vehicle speed V(n) is set to Vmap(n) (Vmap = V). If
the variation in vehicle speed is equal to or lower
than the vehicle speed variation rate limit value of

10   dVlimit at step 205(NO), the routine goes to step 207.
If V- Vmap ≤ dVlimit (namely, V(n) - Vmap(n-1) ≤
dVlimit) (No) at step 203, the routine goes to step
207. Then, at a step 208, controller 4 reads each
vehicle speed dependent constant (yaw rate gain $G\Psi'$,

15   damping coefficient ζ, specific angular frequency ω_n,
and zero-point equivalent value n_1) from each
corresponding control map according to the set map
reference vehicle speed Vmap(n) and the present
process shown in Fig. 7 is ended.

20   [0043]   That is to say, when the control map
representing the correspondence between the vehicle
speed and vehicle speed dependent constant is
referred to, a variation in vehicle speed becomes
moderate and an ill influence of the linear

25   interpolation between the values of the respective
points present on respective maps on the vehicular
motion can be suppressed. In addition, vehicular
velocity variation rate limit value dVlimit is varied
in accordance with absolute value $|\theta|$ of the steering

30   angle so that a situation such that actual vehicle
speed V and map reference vehicle speed Vmap are, at
any time, made different can be avoided. That is to
say, if the steering angle is returned to an

approximately neutral state so that the vehicle runs
on a straight line road to give V = Vmap. Hence,
during the subsequent steering operation, the control
is carried out starting from a state in which each
5   vehicle speed dependent constant tuned previously at
the present vehicle speed is used.

[0044]   (Rear Road Wheel Steering Angle Command
Value Correction Processing)

          Next, rear road wheel steering angle
10   command value calculation and correction processing
to be executed at step 104 shown in Fig. 4 will be
described below.

[0045]   That is to say, under a low vehicle speed
region in which a control effect due to the 4WS
15   steering is low, a tuning approaching to the
characteristic of the two-wheel steering vehicle is
carried out. Hence, rear road wheel steering angle
command value $\delta*$ is calculated to provide
approximately zero. However, as described above,
20   such a case of error that rear road wheel steering
angle command value $\delta*$ that naturally should have
been zeroed has a certain value due to the error
caused by the linear interpolation will occur. To
avoid this, in the low vehicle speed region at which
25   the tuning to approach to naturally the two-wheel
steering (2WS) characteristic, rear road wheel
steering angle command value $\delta*$ is forced to approach
to zero so that the ill influence of the error due to
the linear interpolation is suppressed.

30   [0046]   A rear road wheel steering command value
correction processing will be described with
reference to an operational flowchart shown in Fig. 9.

[0047]   At a step 401, controller 4 determines whether vehicle speed detection value V of the vehicle speed falls below a predetermined vehicle speed B. If V < B at step 401 (Yes), the routine goes to a step 402. If V ≥ B at step 402 (No), the routine goes to a step 407. At a step 402, controller 4 determines whether $|\delta*(n-1)| > \alpha$, wherein an absolute value of previously calculated rear road wheel steering command value $|\delta*(n-1)|$ and α denotes a rear road wheel steering command value convergence quantity. Rear road wheel steering command value convergence quantity α is a value such that a speed for the absolute value of rear road wheel steering angle command value to approach to zero is set and is incremented or decremented to rear road wheel steering angle command value $\delta*$ for each control period. When absolute value of rear road wheel steering angle command value $\delta*$ becomes large, the routine goes from step 402 to a step 403. If $|\delta*(n-1)| \le \alpha$ (No) at step 402, the routine goes to a step 404. At step 403, controller 4 determines if a sign of previously calculated rear road wheel steering angle command value $\delta*(n-1)$ is positive except 0 (> 0). If $\delta*(n-1)$ is positive at step 403, the routine goes to a step 405. If not positive (No) at step 403, the routine goes to a step 406. At step 404, controller 4 sets the present rear road wheel steering angle command value $\delta*(n)$ to zero and the present routine shown in Fig. 9 is ended.

[0048]   At step 405, controller 4 sets a subtraction value of rear road wheel steering angle command value convergence quantity α from previously

calculated rear road wheel steering angle command
value $\delta*(n-1)$ to present rear road wheel steering
angle command value $\delta*(n)$ $(\delta*(n) = \delta*(n-1) - \alpha)$.

[0049]   At step 406, controller 4 sets an addition

5   value of rear road wheel steering angle command value
convergence quantity α to previously calculated rear
road wheel steering angle command value $\delta*(n-1)$ as
the present rear road wheel steering angle command
value $\delta*(n)$ $(\delta*(n) = \delta*(n-1) + \alpha)$. Then, the present

10 routine of Fig. 9 is ended.

[0050]   At step 407, controller 4 calculates
ordinarily a rear road wheel steering angle command
value $\delta*$ (refer to equation (2) described above) as
the present rear road wheel steering angle command

15 value $\delta*(n)$. Then, the present routine in Fig. 9 is
ended.

[0051]   As described above, it is possible to set
accurately rear road wheel steering angle command
value $\delta*$ to zero under a low vehicle speed region

20 (lower than predetermined vehicle speed B). It
becomes possible to eliminate the influence of the
error caused by the linear interpolation when each
vehicle speed dependent constant is set. A desired
characteristic can, thus, be obtained. In addition,

25 since rear road wheel steering angle command value
convergence quantity α is set and a moderate
convergence of rear road wheel steering angle command
value $\delta*$ into zero can prevent such a phenomenon that
the rear road wheel steering angle becomes abruptly

30 zeroed and that the sense of incompatibility is given
to the vehicle driver.

[0052]   (Simulation)

Figs. 10A through 10F show simulation results indicating the respective control signals and the vehicular motion in a case where vehicle speed variation rate limitation is not placed (with no vehicle speed variation rate limiter) for the detection value of the vehicle speed V to directly become the map reference vehicle speed Vmap. In addition, Figs. 11A through 11F show each control signal and vehicular motion when the vehicle speed variation rate limitation is placed (with the vehicle speed variation rate limiter provided) for each speed dependent constant.

[0053]   When the vehicle was decelerated from a point A of vehicular speed, a steering operation of 45° was carried out at a time point of t1 and a deceleration of about 0.28G was carried out at a time point of t2. In addition, yaw rate gain $G\Psi'$ as one of vehicle speed dependent constants indicated the characteristics shown in Fig. 5, specific angular frequency ωn, zero-point equivalent value n_1, and damping constant ζ indicated the approximately same characteristics as 2WS in a range below vehicle speed A. In a case where, as appreciated from Figs. 10A through 10F, the limitation on the vehicle speed variation rate is not placed, a variation of target yaw angular acceleration $\Psi''*$ was large and rear road wheel steering angle command value $\delta*$ was varied.

[0054]   On the other hand, in the case of the present invention, namely, in the case where the limitation on the vehicle speed variation rate was placed, the variation of each control signal was suppressed. Consequently, as shown in Figs. 11A

through 11F, a difference in the variation in the lateral acceleration dV_y developed on the vehicle appeared. In the case of the present invention, it will be appreciated that the influence of each control signal given to the driver was suppressed. It is noted that a subscript M of each control signal shown in Figs. 10A through 11F denotes the simulation result.

[0055] (Other Embodiments)

As described above, the vehicular motion control apparatus according to the present invention is not limited to the first embodiment described above. For example, the present invention is applicable to a vehicle in which a front road wheel steering angle providing section is mounted to provide the front road wheels with an auxiliary steering angle. Furthermore, the present invention is applicable to a vehicle in which a braking control section which is capable of controlling the vehicular yaw rate using a brake pressure difference between the left and right brake wheels. If the vehicular speed variation rate limiter is applied to each of the vehicles described above, a control target value (for example, target yaw rate, target lateral speed, or so on) is not varied quickly or abruptly. A further stable vehicular motion control can be achieved.

[0057] It is noted that front road wheel steering angle sensor 14 corresponds to a steering angle detecting section, rear road wheel steering angle sensor 17 corresponds to a state detecting section in a broad sense of term, drive motor 11 corresponds to a rear road wheel steering actuator in a broad sense

of term, steering angle variable mechanism 3
corresponds to a vehicular motion control mechanism,
a rear road wheel steering angle providing section,
and vehicular motion controlling means, in a broad
5   sense of term, vehicular target value setting section
41 corresponds to a vehicular motion target value
calculating section (means), in a broad sense of term,
rear road wheel steering angle command value
calculating section 42 corresponds to a control
10 command value calculating section (means), in a broad
sense of term, and rear road wheel steering angle
servo calculating section 43 corresponds to a servo
calculating section(means), in a broad sense of term.
It is also noted that target rear road wheel steering
15 angle $\delta*$ recited in equation (2) has the same meaning
as rear road wheel steering angle command value $\delta*$
recited in rear road wheel steering command value
calculating section 42 and rear road wheel steering
angle servo calculating section 43.
20 [0058]   The entire contents of a Japanese Patent
Application No. 2003-031556 (filed in Japan on
February 7, 2003) are herein incorporated by
reference. The scope of the invention is defined with
reference to the following claims.

25

30